

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

**Trade name/designation**

061 Ripcare weiss  
UFI: QT1W-U0ET-K004-CF1D

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

Adhesives, sealants

**1.3 Details of the supplier of the safety data sheet**

**Supplier**

Delta Distribution GmbH  
Am Heuberg 25 Telephone: +49-364-179972581  
37308 Schimberg E-mail: hello@delta-dist.eu  
Germany Website: www.delta-dist.eu

**Department responsible for information**

E-mail (competent person) hello@delta-dist.eu

**1.4 Emergency telephone number**

24 hr. emergency phone number: +49 361-730730

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2; flammable liquids; H225 Highly flammable liquid and vapour.

Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation.

STOT SE 3 Narcotic effects; STOT-single exposure; H336 May cause drowsiness or dizziness.

**2.2 Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



GHS02 GHS07

**Signal word**

Danger

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**\* Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapours.  
P280 Wear protective gloves and eye protection/face protection.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**Hazard components for labelling**

acetone; propan-2-one; propanone

**Supplemental hazard information**

\* not applicable

**2.3 Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

**SECTION 3: Composition/information on ingredients.**

**3.2 Mixtures**

**Description**

Polyurethane-prepolymers with stabilizers and filling materials in a mixture of organic solvents

**Hazardous ingredients**

| CAS No.<br>EC No.<br>Index No.             | Substance name<br>REACH No.<br>Classification according to Regulation (EC) No 1272/2008 [CLP]                                                                                                                                    | weight-%    |
|--------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| *<br>141-78-6<br>205-500-4<br>607-022-00-5 | <b>ethyl acetate</b><br>01-2119475103-46<br>Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066<br>ATE (oral): > 5,620 mg/kg<br>ATE (dermal): > 18,000 mg/kg<br>ATE (inhalative): = 56 mg/L (4 h)                    | 25,0 < 35,0 |
| *<br>67-64-1<br>200-662-2<br>606-001-00-8  | <b>acetone; propan-2-one; propanone</b><br>01-2119471330-49<br>Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066<br>ATE (oral): = 5,800 mg/kg<br>ATE (dermal): > 15,800 mg/kg<br>ATE (inhalative): = 76 ppmV (4 h) | 25,0 < 35,0 |
| *<br>123-86-4<br>204-658-1<br>607-025-00-1 | <b>n-butyl acetate</b><br>01-2119485493-29<br>Flam. Liq. 3 H226 / STOT SE 3 H336 / EUH066                                                                                                                                        | 1,0 < 5,0   |

**Remark**

Full text of H- and EUH-statements: see section 16. Full text of H-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

- \* In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**Following inhalation**

- \* Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

- \* Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

- \* Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

- \* If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

**Symptoms**

- \* In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3 Indication of any immediate medical attention and special treatment needed**

- \* First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

- \* alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Powder, spray mist, (water)

**Unsuitable extinguishing media**

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)

## according to Regulation (EU) 2020/878

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

\* Strong water jet

### 5.2 Special hazards arising from the substance or mixture

\* Inhaling hazardous decomposing products can cause serious health damage. Flammable. Vapours can form explosive mixtures with air.

### 5.3 Advice for firefighters

\* Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

\* Ventilate affected area. Do not breathe vapours.

### 6.2 Environmental precautions

\* Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For containment

\* Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

\* Clean using cleansing agents. Do not use solvents.

### 6.4 Reference to other sections

\* Safe handling: see section 7  
Personal protection equipment: refer to section 8  
Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advices on safe handling

\* Avoid contact with skin, eyes and clothes. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Advices on general occupational hygiene

\* When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

\* Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### Hints on joint storage

\* Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Storage class** LGK3 - Flammable liquids

#### Further information on storage conditions

\* Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between 10 °C and 30 °C.

### 7.3 Specific end use(s)

\* Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

| CAS No.   | Substance name                   | Source | Long-term /short-term (Spitzenbegrenzung) |
|-----------|----------------------------------|--------|-------------------------------------------|
| * 67-64-1 | acetone; propan-2-one; propanone | WEL    | 1,210 / 3,620 ( - ) mg/m <sup>3</sup>     |

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

|   |          |               |     |                                     |
|---|----------|---------------|-----|-------------------------------------|
| * | 141-78-6 | ethyl acetate | WEL | 734 / 1,468 ( - ) mg/m <sup>3</sup> |
|---|----------|---------------|-----|-------------------------------------|

**Additional information**

Long-term: Long-term occupational exposure limit value  
short-term: short-term occupational exposure limit value

**Biological limit values**

No data available

**DNEL worker**

|   | CAS No.  | Substance name                   | DNEL type                            | DNEL value |
|---|----------|----------------------------------|--------------------------------------|------------|
| * | 67-64-1  | acetone; propan-2-one; propanone | DNEL acute inhalative (systemic)     | 2,420 mg/L |
| * | 67-64-1  | acetone; propan-2-one; propanone | DNEL long-term inhalative (systemic) | 1,210 mg/L |
|   | 67-64-1  | acetone; propan-2-one; propanone | DNEL long-term dermal (systemic)     | 186 mg/kg  |
| * | 141-78-6 | ethyl acetate                    | DNEL long-term inhalative (systemic) | 1.468 mg/L |
| * | 141-78-6 | ethyl acetate                    | DNEL acute inhalative (local)        | 1.468 mg/L |
|   | 141-78-6 | ethyl acetate                    | DNEL long-term dermal (systemic)     | 63 mg/kg   |

**DNEL Consumer**

|   | CAS No.  | Substance name                   | DNEL type                            | DNEL value |
|---|----------|----------------------------------|--------------------------------------|------------|
|   | 67-64-1  | acetone; propan-2-one; propanone | DNEL long-term dermal (systemic)     | 62 mg/kg   |
|   | 67-64-1  | acetone; propan-2-one; propanone | DNEL long-term inhalative (systemic) | 200 mg/L   |
|   | 67-64-1  | acetone; propan-2-one; propanone | DNEL long-term oral (repeated)       | 62 mg/kg   |
| * | 141-78-6 | ethyl acetate                    | DNEL acute inhalative (systemic)     | 0.734 mg/L |
| * | 141-78-6 | ethyl acetate                    | DNEL long-term inhalative (local)    | 0.734 mg/L |
|   | 141-78-6 | ethyl acetate                    | DNEL long-term dermal (systemic)     | 37 mg/kg   |
| * | 141-78-6 | ethyl acetate                    | DNEL long-term inhalative (systemic) | 0.037 mg/L |
| * | 141-78-6 | ethyl acetate                    | DNEL long-term oral (repeated)       | 4.5 mg/kg  |
| * | 141-78-6 | ethyl acetate                    | DNEL acute inhalative (local)        | 0.367 mg/L |

**PNEC**

|   | CAS No.  | Substance name                   | PNEC type                   | PNEC Value  |
|---|----------|----------------------------------|-----------------------------|-------------|
| * | 67-64-1  | acetone; propan-2-one; propanone | PNEC aquatic, freshwater    | 10.6 mg/L   |
| * | 67-64-1  | acetone; propan-2-one; propanone | PNEC aquatic, marine water  | 1.06 mg/L   |
| * | 67-64-1  | acetone; propan-2-one; propanone | PNEC sediment, freshwater   | 30.4 mg/L   |
| * | 67-64-1  | acetone; propan-2-one; propanone | PNEC sediment, marine water | 3.04 mg/L   |
| * | 67-64-1  | acetone; propan-2-one; propanone | PNEC soil, marine water     | 29.5 mg/L   |
| * | 141-78-6 | ethyl acetate                    | PNEC aquatic, freshwater    | 0.26 mg/L   |
| * | 141-78-6 | ethyl acetate                    | PNEC aquatic, marine water  | 0.026 mg/L  |
| * | 141-78-6 | ethyl acetate                    | PNEC sediment, freshwater   | 0.34 mg/kg  |
| * | 141-78-6 | ethyl acetate                    | PNEC sediment, marine water | 0.034 mg/kg |
| * | 141-78-6 | ethyl acetate                    | PNEC soil, freshwater       | 0.22 mg/kg  |

**8.2 Exposure controls**

Provide good ventilation. This can be achieved with local or room suction.

**Personal protection equipment**

**Respiratory protection**

- \* Respiratory protection necessary at: insufficient ventilation Suitable respiratory protection apparatus: Combination filtering device AX EN 14387
- \* A

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

**Hand protection**

Suitable material: NBR (Nitrile rubber)  
Thickness of the glove material  $\geq 0.4$  mm  
Breakthrough time  $\geq 480$  min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

**Skin protection**

- \* Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

- \* Eye glasses with side protection

**Body protection**

- \* When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

**Environmental exposure controls**

- \* Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

|                                         |                |
|-----------------------------------------|----------------|
| Physical state                          | Liquid         |
| Colour                                  | transparent    |
| Odour                                   | characteristic |
| pH at 20 °C                             | not determined |
| Melting point/freezing point            | not determined |
| Initial boiling point and boiling range | 56 °C          |
| Flash point                             | < -20 °C       |
| flammability                            | not applicable |
| Lower explosion limit at 20°C           | 2.1 Vol-%      |
| Upper explosion limit at 20°C           | 14.3 Vol-%     |
| Vapour pressure at 20°C                 | 246 mbar       |
| Relative vapour density                 | not applicable |
| Density at 20 °C                        | 0.934 kg/L     |
| Water solubility at 20°C                | not determined |
| Partition coefficient: n-octanol/water  | see section 12 |
| Ignition temperature in °C              | 460 °C         |
| Decomposition temperature               | not determined |
| Dynamic viscosity at 20 °C              | 31,000         |

**9.2 Other information**

not applicable

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

- \* No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability**

- \* Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

**10.3 Possibility of hazardous reactions**

- \* Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

**10.4 Conditions to avoid**

- \* Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

**10.5 Incompatible materials**

- \* No further relevant information available.

**10.6 Hazardous decomposition products**

- \* Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide, smoke.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

- \* **acetone; propan-2-one; propanone**

LD50: oral (Rat): = 5,800 mg/kg

- \* LD50: dermal (Rabbit): > 15,800 mg/kg

LC50: inhalative (Rat): = 76 ppmV (4 h)

- \* **ethyl acetate**

LD50: oral (Rat): > 5,620 mg/kg

- \* LD50: dermal (Rabbit): > 18,000 mg/kg

LC50: inhalative (Rat): = 56 mg/L (4 h)

**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

- \* **Overall assessment on CMR properties**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**11.2 Information on other hazards**

- \* **Endocrine disrupting properties**

- \* This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Based on available data, the classification criteria are not met.

**Acute (short-term) fish toxicity**

- \* **acetone; propan-2-one; propanone**

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 5,540 mg/L (96 h)

**ethyl acetate**

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 230 mg/L (96 h)

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

**Acute (short-term) toxicity to algae and cyanobacteria**  
**acetone; propan-2-one; propanone**  
ErC50: = 100 mg/L (96 h)

- \* **ethyl acetate**  
LC50: (Desmodesmus subspicatus): = 5,600 mg/L (48 h)

- \* **Acute (short-term) toxicity to aquatic invertebrates**  
**acetone; propan-2-one; propanone**  
EC50 (Daphnia pulex (water flea)): = 8,800 mg/L (48 h)

**ethyl acetate**  
EC50 (Daphnia magna (Big water flea)): = 165 mg/L (48 h)

**12.2 Persistence and degradability**

No information available.

**12.3 Bioaccumulative potential**

- \* Partition coefficient: n-octanol/water = -0.24 (acetone; propan-2-one; propanone)
- \* Partition coefficient: n-octanol/water = 2.3 (n-butyl acetate)
- \* Partition coefficient: n-octanol/water = 0.68 (ethyl acetate)

**12.4 Mobility in soil**

No information available.

**12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6\* Endocrine disrupting properties**

No information available.

**12.7 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

- \* **Product/Packaging disposal**  
Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
**Waste codes/waste designations according to EWC/AVV**  
080409\* - Waste adhesives and sealants containing organic solvents or other dangerous substances  
**Other disposal recommendations**  
Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1 UN number or ID number**

UN 1133

**14.2 UN proper shipping name**

**Land transport (ADR/RID)**

- \* Adhesives (acetone; propan-2-one; propanone, ethyl acetate)

**Sea transport (IMDG)**

- \* Adhesives (contains acetone; propan-2-one; propanone, ethyl acetate)

**Air transport (ICAO-TI / IATA-DGR)**

- \* Adhesives (contains acetone; propan-2-one; propanone, ethyl acetate)

**14.3 Transport hazard class(es)**

|                                    |   |
|------------------------------------|---|
| Land transport (ADR/RID)           | 3 |
| Sea transport (IMDG)               | 3 |
| Air transport (ICAO-TI / IATA-DGR) | 3 |

**14.4 Packing group**

|                          |                                  |
|--------------------------|----------------------------------|
| Land transport (ADR/RID) | II                               |
|                          | for packages < = 450 litres: III |
| * Sea transport (IMDG)   | II                               |
|                          | for packages < = 450 litres: III |

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

Air transport (ICAO-TI / IATA-DGR) II  
for packages < 30 litres:III

**14.5 Environmental hazards**

Land transport (ADR/RID) not applicable  
Sea transport (IMDG) not applicable

**14.6 Special precautions for user**

- \* Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.  
Advices on safe handling: see parts 6 - 8

**14.7 Maritime transport in bulk according to IMO instruments**

No transport as bulk according to IBC Code.

**14.8 Additional information**

**Land transport (ADR/RID)**

Tunnel restriction code: D/E for packages < = 450 litres: E

- \* Special Provisions: SV 640C  
Limited quantity (LQ): 5 ltr  
Hazard identification number (Kemler No.): 33

**Sea transport (IMDG)**

- \* EmS-No.: F-E, S-D  
Limited quantity (LQ): 5 ltr

**Air transport (ICAO-TI / IATA-DGR)**

not applicable

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Restrictions of occupation**

- \* Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.  
Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**

- \* VOC value: 625 g/l

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**

**Hazard categories / Named dangerous substances**

- \* P5c FLAMMABLE LIQUIDS  
Quantity 1: 5,000t; Quantity 2: 50,000t

**National regulations**

- \* Observe in addition any national regulations!

**15.2 Chemical Safety Assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

|   | REACH No.        | Substance name                   | CAS No.<br>EC No.     |
|---|------------------|----------------------------------|-----------------------|
| * | 01-2119471330-49 | acetone; propan-2-one; propanone | 67-64-1<br>200-662-2  |
| * | 01-2119475103-46 | ethyl acetate                    | 141-78-6<br>205-500-4 |
| * | 01-2119485493-29 | n-butyl acetate                  | 123-86-4<br>204-658-1 |

**SECTION 16: Other information**

**List of relevant hazard statements and/or precautionary statements from sections 2 to 15**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- \* EUH066 Repeated exposure may cause skin dryness or cracking.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

061  
Version 2.0

Ripcare weiss  
Revision date 18 Jul 2025

Print date 28 Jul 2025

**Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

|                            |                        |
|----------------------------|------------------------|
| Flam. Liq. 2               | On basis of test data. |
| Eye Irrit. 2               | Calculation method.    |
| STOT SE 3 Narcotic effects | Calculation method.    |

**Abbreviations and acronyms**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

**Indication of changes**

\* Data changed compared with the previous version.